presto Polish- and Grinding Paste

Technical Information



To remove spray mist and to level paint repair to old paint finish. Cleans at the same time weathered lacquer and gives a new bright shine to the lacquer. Ingredient carnauba wax grants conservation for months.

Ord.-no: 603192

Quality & properties

High gloss development
Good grinding behaviour
Silicone-free
Conserves the paint finish
Can be mixed with water

Physical & chemical data

Base: See MSDS
Colourname: beige
Minimum Working Temperature: 5 °C
Maximum Working Temperature: 30 °C
pH value: 7,8
Flash point: >70
Storage stability: 2 years

How to use

The surface you want to polish has to be clean and dry.
We recommend to test the compatibility of the product at an invisible spot.
Apply a thin coat of the presto polishing paste by means of a lint-free cloth, then smooth evenly.
Polish to high gloss with a soft cloth or with batting after a short drying time.
Do not work in the sun or on warm surfaces.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as “special refuse”.

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of January 26, 2026 – This release replaces all eventually earlier issued versions.

European Aerosols GmbH, Kurt-Vogelsang-Straße 6, 74855 Haßmersheim – info-de@european-aerosols.com
European Aerosols B.V., Wolfraamweg 2, NL-8471 XC Wolvega – info-nl@european-aerosols.com