DUPLI-COLOR Galvinol

Technical Information



Special primer improving the adhesion on very smooth and non-porous surfaces. Remains sticky at the surface and forms the perfect adhesion promoter for the subsequent painting with DUPLI-COLOR Alkyton RUST PROTECTION.

Ord.-no: 334337, 334344

Quality & properties

Solvent containing special primer
For brush application
Forms a sticky surface as adhesion promoter

Physical & chemical data

Base: Acrylic resin
Colourname: transparent
Smell: Characteristic
Minimum Working Temperature: 5 °C
Maximum Working Temperature: 35 °C
Flash point: -4
Storage stability: 5 years
Content:
- 250 ML
- 750 ML

European Aerosols GmbH, Kurt-Vogelsang-Straße 6, 74855 Haßmersheim – info-de@european-aerosols.com
European Aerosols B.V., Wolfraamweg 2, NL-8471 XC Wolvega – info-nl@european-aerosols.com

How to use

Remove oil, grease and all other surface contaminations by alkaline or high pressure (steam), cleaning in combination with appropriate detergents.
Remove previous coatings completely. Use depending on necessity a wire brush, sand blasting or sand paper.
The surface must be clean and dry during application.
To ensure homogeneity, the lacquer should be thoroughly stirred prior to use.
DUPLI-COLOR GALVINOL Special Primer is intended for brush application.
Application by air-atomised spraying or airless spraying is not recommended.
Use natural bristles, long hair brushes.
Apply the primer in very thin uniform layers.
Apply in well-ventilated areas.
During application the surrounding area, the substrate and the adhesion primer should have a temperature above 5°C and below 35°C.
Apply the top coat earliest after 30 minutes, but within 24 hours. The longer you wait, the bigger the risk to include particles of dust and dirt in the sticky surface.
Cleanup: Use white spirit
Application conditions:
Temperature of air, substrate and coating material: between 5° and 35 °C
Relative air humidity: below 85 %
Substrate temperature: at least 3°C above dew point.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as “special refuse”.

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of August 4, 2025 – This release replaces all eventually earlier issued versions.

European Aerosols GmbH, Kurt-Vogelsang-Straße 6, 74855 Haßmersheim – info-de@european-aerosols.com
European Aerosols B.V., Wolfraamweg 2, NL-8471 XC Wolvega – info-nl@european-aerosols.com