TYTAN Professional Flexi Gum – Liquid Rubber

Aerosol Flexi Gum Liquid Rubber – is an easy to use product quick filling and sealing leaks and cracks. It creates an elastic waterproof layer that prevents the penetration of moisture and the occurrence of corrosion.

ADVANTAGES

- Suitable for most surfaces, including: metal, galvanized, aluminum, concrete, wood, ceramic; as well as for use on bituminous roofing, masonry, etc.
- Can be over painted (with water, latex or oil based paint)
- Fast drying
- Protects against moisture and corrosion
- Easy and quick to apply

TECHNICAL INFORMATION

Color:	black, transparent
Base:	synthetic rubber
propellant:	propan/butan
working temperature:	+10°C - +35°C
Can temperature:	+5°C - +35°C
Temperature resistance:	-40°C - + 50°C
Time*:	
- dry to touch:	20-30 minute
- to next layer apply:	after 15-30 minutes
- full hardness:	after approx. 72 hours
- coverage:	0,7-0,8 m2/400 ml

* at 20°C, 50% relative air humidity

APPLICATION

Remove all dust, dirt, grease and oil stains, salt and chemical contamination with detergents or other suitable cleaning methods. Rinse with clean water and dry the surface. If necessary use the stiff brush or sandpaper to remove rest of old paint and rust. Apply product on absolutely dry surface. Shake the can vigorously for 1 minute at least. Make a spray test on a cardboard for better control of the spray. Apply layers with short strokes, holding the spray distance 15-30 cm from the surface. After 15-30 minutes it is recommended to apply the second layer to achieve the best result.
After use, turn can upside down and press the sprayer to clean the valve.

Selena FM S.A. ul. Strzegomska 2-4, 53-611 Wrocław, Poland
tel.: +48 71 78 38 290, fax: +48 71 78 38 291
e-mail: info@selenafm.com, www.selenafm.com

ADDITIONAL INFORMATION

Shake the can vigorously for 1 minute after the mixing ball begins to roll. It is recommended to test spray before use.
For best results, it is recommended to apply the first layer with a thinner one, the next one with a thicker one. The appearance of bubbles and foaming are normal and disappear as the surface dries.
If the valve is clogged, twist and remove the nozzle, wash it with a solvent, for example, white spirit.

CONDITIONS OF USE AND STORAGE

Use outside or in well ventilated areas. Spray at + 10 ° C to + 35 ° C and humidity below 85% to ensure proper drying. Do not apply to surfaces heated to temperatures above 90 ° C. Use only during dry weather, in places protected from the wind.
Expiration date – 10 years from the date of production. Store in a dry, well-ventilated area at a temperature from + 5 ° C to + 35 ° C, avoid exposure to sunlight.
Do not pierce or burn container even after use.

12/05/2019
With the publication of this Technical Data Sheet, previous editions are no longer valid.

The information contained herein is offered in good faith based on Selena's research and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information shall not be used in substitution for customer's tests to ensure that Selena's products are fully satisfactory for your specific applications. Selena's sole warranty is that the product will meet its current sales specifications. Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted. Selena Co. S.A. specifically disclaims any other expressed or implied warranty of fitness for a particular purpose or merchantability. Selena disclaims liability for any incidental or consequential damages. Suggestions of use shall not be taken as inducements to infringe any patent.

SELENA GLOBAL EXPERIENCE
Selena FM S.A. ul. Strzegomska 2-4, 53-611 Wrocław, Poland
tel.: +48 71 78 38 290, fax: +48 71 78 38 291
e-mail: info@selenafm.com, www.selenafm.com